




Freze YG1 din carbura, varianta extralunga, 4 dinti:

- ▶ Ideal pentru aplicatii de aschiere uscate la temperaturi mari
- ▶ Freze de o performanta excelenta
- ▶ 4 dinti care permit o mai buna finisare a suprafatei



Unit : mm

Cod	Ø	Ø coada	L activa	L totala	Stoc
G9453903	3.0	3	20	60	5
G9453904	4.0	4	20	60	1
G9453905	5.0	5	25	75	4
G9453906	6.0	6	30	75	3
G9453908	8.0	8	30	75	3
G9453910	10.0	10	40	100	3
G9453912	12.0	12	45	100	0
G9453914	14.0	14	45	100	3
G9453916	16.0	16	45	100	1
G9453918	18.0	18	45	100	2
G9453920	20.0	20	45	100	2

Toleranta dia L activa	Toleranta dia coada
0~-0.03	h6

Materiale in care se poate lucra:

◎ : Excellent ○ : Bun

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel	Acrylic	CFRP
~HB225	HB225~325	HRc30~40	HRc40~45	HRc45~55	HRc55~70									
◎	◎	◎				○		○	○	○	○	○		