




Freze YG1 din carbura, varianta scurta, 4 dinti:

- ▶ Ideal pentru aplicatii de aschiere uscate la temperaturi mari
- ▶ Freze de o performanta excelenta
- ▶ 4 dinti care permit o mai buna finisare a suprafatei



Unit : mm

Cod	Ø	Ø coada	L activ	L totala	Stoc
G9A69010	1.0	3	3	39	0
G9A69015	1.5	3	5	39	0
G9A69020	2.0	3	7	39	0
G9A69025	2.5	3	7	39	0
G9A69030	3.0	3	10	39	3
G9A69040	4.0	4	14	51	3
G9A69050	5.0	5	16	51	3
G9A69060	6.0	6	19	64	0
G9A69080	8.0	8	21	64	0
G9A69100	10.0	10	22	70	0
G9A69120	12.0	12	25	76	0
G9A69160	16.0	16	32	89	0
G9A69200	20.0	20	38	102	0

Toleranta dia L activa	Toleranta dia coada
0~-0.03	h6

Materialele in care se poate lucra:

◎ : Excellent ○ : Bun

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel	Acrylic	CFRP
~HB225	HB225~325	HRc30~40	HRc40~45	HRc45~55	HRc55~70									
◎	◎	◎				○		○	○	○	○	○		